



EX - FLOODLIGHTS FOR HIGH PRESSURE DISCHARGE LAMPS



PX ...

Technical data

Certificate	LOM 03 ATEX 2078
Type of protection	II 2 G EEx de IIC
Temperature class	T2-T3
Protection category to EN 60529	IP 67
Insulation class	I
Rated voltage	230 V / 50 Hz
Connecting terminals	L1, N – 2x4mm ² PE – 2x6mm ²
Cable entries	1 x M25 , 1 x plug M25
Lamp holder	E 40
Permissible ambient temperature	-20 °C to +55 °C

Temperature class

Temperature class	LAMP	
T2	Sodium vap. high press. lamp	600 W
T2	Mixed light lamp	500 W
T2	Halogene lamp with prot. bulb	500 W
T3	Sodium vap. high press. lamp	400 W
T3	Halogen high press.metal-vap.	400 W
T3	Sodium vap. high press. lamp	250 W
T3	Halogen high press.metal-vap.	250W
T3	Sodium vap. high press. lamp	150 W
T3	Halogen high press.metal-vap.	150 W

Type	Lamp	Cable entry	Order code
PX 60	HST	2x M25	NOR000115170143
PX 40	HST, HIT.	2x M25	NOR000115170144
PX 25	HST, HIT..	2x M25	NOR000115170145
PX 15	HST, HIT.	2x M25	NOR000115170146
PX 05	QT, HME-SB	2x M25	NOR000115170148

Dimensions

